

snom[®] MeetingPoint

snom OCS[®]
edition

klarVOICE[®]
EXCELLENT AUDIO QUALITY

OmniSound[®]

CTI
inside



- **OmniSound[®] full duplex wideband sound technology**
- **Management of up to 4 external participants**
- **Recording range up to 30 m² or 10 participants**
- **Simultaneous management of internal and external telephone listings (LDAP)**
- **Extra microphone connection for wider reception**
- **Microsoft Office Communication Server 2007 R2 ready**
- **Multiple SIP registrations**
- **Open VPN**

The first VoIP conference telephone from snom, the snom MeetingPoint, is the ideal complement for everyone who frequently needs to make multi-location arrangements. The snom MeetingPoint allows you to have up to 4 parties at different locations all over the world attend your conference - without slow-mail delays and without costly travel expenses. Protect your travel budget and the environment at the same time!

Of course, the snom MeetingPoint provides the additional comfort, that you would expect from snom: management of up to 4 external

participants, LDAP, contact listings, possible snom Flexor CTI integration, excellent sound by OmniSound[®] 2.0 etc.

The snom MeetingPoint is perfectly qualified for use in medium to large conference rooms. Thanks to its reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences with large groups of up to 10 persons without adversely affecting the intelligibility of the call. Three speakers, equipped with full duplex wideband audio (7 kHz, codec "G.722"), provide bal-

anced and full sound which snom customers already know from the snom klarVOICE handset. The integrated special microphones ensure that your interlocutors feel as if you are sitting in the neighboring office - and not on the other side of the world!

The graceful styling of the snom MeetingPoint integrates ideally into each VoIP infrastructure and makes it a subtle eye-catcher for your conference room.

TECHNICAL DATA **snom** MeetingPoint

GENERAL FEATURES

- **Size:** Diameter: 240 mm, Height: 77 mm
- **Display:** Background-lit graphical LCD, 128x64 pixels
- **Weight:** 1 kg
- **Color:** black
- **Keypad:** Alphanumeric 0-9, *, #, dial, hang up, mute, increase volume, menu, conference, recording, volume control, 5 keys for navigation in the menu system
- **Microphone:** circular (360°) recording characteristics
- **Reception range:** up to 30 m², < 10 persons
- **Speaker:** Frequency range: 150-15000 Hz playback
- **Volume:** 90 db SPL 0.5m. Equalizer function
- **Anti-theft protection:** Kensington security slot

CONNECTIONS

- **Network connection:** 1x RJ-45, PoE 10/100MBit
- **Power supply:** Power adapter 100-240 V AC/14 V DC - PoE
- **External microphones:** modular 4/4 possible

SURROUNDING CONDITIONS

- **Temperature:** 5°–40° Celcius
- **Air humidity:** 20–80%
- **Recommended acoustic room conditions:**
Reverberation time: 0.5 S Rt 60
Background noise: 45 dbA

SUPPORTED STANDARDS

- **Telekom:** TBR21, 47 CFR part 68/TIA, IC CS-03 Issue 1999/01/01
- **EMC:** EN301 489-1,3. EN 300 220-1,2, FCC subpart B und C.
- **Electrical safety class:** UL 60950-1, EN 60950-1:200



snom technology AG

Charlottenstraße 68–71
10117 Berlin
tel/enum: +49 30 39833-0
fax: +49 30 39833-111
sip: info@snom.com
mail: info@snom.com